

## PATENT ABSTRACTS OF JAPAN

(11)Publication number : 03-000114

(43)Date of publication of application : 07.01.1991

(51)Int.Cl.

B01D 65/02

B01D 63/02

(21)Application number : 01-132330

(71)Applicant : AKUA RUNESANSU GIJUTSU  
KENKYU KUMIAI

(22)Date of filing : 24.05.1989

(72)Inventor : MATSUI KOJI  
TAKADONO SUMIO  
TAWARA SHINJI  
IKEHATA HISASHI  
OTANI HAJIME**(54) METHOD FOR CLEANING HOLLOW-FIBER MEMBRANE MODULE****(57)Abstract:**

**PURPOSE:** To reduce cleaning time and to easily maintain the initial permeability of the membrane by emptying out the inside of a cylindrical case to contain a hollow-fiber membrane bundle and exerting a back pressure from the permeation side to clean the membrane module.

**CONSTITUTION:** The hollow-fiber membrane bundle 12 is placed in the cylindrical case 11, the inside of the case 11 is used as the raw liq. chamber and the inside of the hollow-fiber membrane as the permeation side to constitute the hollow-fiber membrane module 1. The module 1 is cleaned at regular time intervals during its filtration operation. In that case, the inside of the case 11 is emptied out, a back pressure is exerted from the permeation side to force the permeated liq. in the backwashing tank into the hollow-fiber membrane, and backwashing is performed. As a result, cleaning time is reduced, and the membrane can be cleaned at regular time intervals during its operation without substantially hindering the operational continuity.

